

ARCHITECTURAL

**GRATES + DRAINS** 

Code 38PS40

Grate Style PS

Steel Grade 316

dimensions.

Range Special Assembly

**Category** Components

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over

3000mm supplied in sections with joiner. +/-2mm tolerance on



## 38PS40 Linear Drain

This is our Punched Slot grate for use with the 38G90 and 38G100 Special Assembly drain.

A 38mm wide UPVC channel is connected via downpipes at 200mm intervals to sockets in a 90mm or 100mm drain below. This allows the channel to be installed level while the drainpipe is given sufficient fall to be self-cleaning.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

This unique drainage system was recognised for its innovation by a DesignMark at the Australian International Design Awards.

## **SPECIFICATIONS + DIMENSIONS**

Channel Width Channel Depth Length(s) Outlet Size 38mm 40mm 900mm 1000mm 1200mm 1500mm N/A

## STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

## **PRODUCT APPLICATIONS**

Bathroom Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Pool and Spa Area Drainage Paved Area Drainage Shower Drainage Special Needs Drainage Threshold Drainage Suspended Slab Drainage Wet Area Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 16/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

\_\_\_\_\_